

????? ???????????????:

- ????:
- ???????????????:
- ??????: OCEM 1440
- ??? ???????:

??????????????:



??????????????:

<!--[if gte mso 9]><xml> </xml><![endif]-->

Installation for the production of with capacity for 1.000m²/turn. Model OCEM 1440terrazzo tiles. This installation includes the following equipment:

- 1 Concrete plant composed by
FAIR FACE
 - 3 hoppers 2.500x2.500 with vibrating chutes in joint chassis
 - 1 weight feeder with 4 load cells
 - 2 conveyor belts to elevate material to the mixer
 - 1 rotary mixer for 250 L.
 - 1 chute from the mixer to the doser
 - 1 worm conveyor for cement**BACK FACE**
 - 2 hoppers 2.500x2.500 with vibrating chutes in joint chassis
 - 1 weight feeder with 4 load cells
 - 2 conveyor belts to elevate material to the rotary mixer of 250 l.
 - 1 chute from the mixer to the back doser
 - Full electric panel
- 1 OCEM press model OPA-1440 , in operation when unmounted, consisting on
 - 1 back face carriage
 - 1 bucket conveyor and extractor belt for the back side surplus material
 - 1 hidraulic central
 - 1 pneumatic unit
 - 1 set of moulds for 1/400x400 mm



: IN0230415

- 1 mix spreader
- 1 electric switchboard with automation
- 1 mix doser OPA-1440

- 1 vertical single extractor, composed by
 - 1 full pallet stacker
 - Extractor carriage
 - 1 empty pallet stacker
 - 1 intermediate gear
 - 1 electric installation
 - 1 electric switchboard
 -

- 1 complete set of 40cmx40cm moulds

- A variety of pallets with rubber backs with different finishes, for different tile formats; 40cmx40cm, 30cmx30cm, 25cmx25cm...

- +/- 500 trays for pavement stacking and drying